

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER(S): IPAC AWHO (ISO GRADES 32, 46, 68, 100)

COMPANY IDENTIFICATION

EMERGENCY TELEPHONE NUMBERS

International Petroleum Products
& Additives Company, Inc (IPAC)
7600 Dublin Blvd. Suite 240
Dublin, CA 94568

HEALTH (24 hr): (925) 556-5530

PRODUCT INFORMATION: MSDS Requests: (925) 556-5530
Environmental, Safety, & Health Info.: (925) 556-5530
Product Information(925) 556-5530

2. COMPOSITION/INFORMATION ON INGREDIENTS

IPAC AWHO (ISO GRADES 32, 46, 68, 100)
CONTAINING

COMPONENT	CAS NUMBER	TLV/PEL (mg/M3)	WEIGHT %
PETROLEUM OIL	64742-58-1	NA	67-68
PROPRIETARY ADDITIVES	MIXTURE	NA	1-2
SOLVENT DEWAXED	8012-95-1	NA	32-33

3. HAZARDS IDENTIFICATION

***** **EMERGENCY OVERVIEW** *****

Oral : LD50 (rat): >15g/kg
Eye: Practically Non-Irritating
Skin: Practically Non-Irritating
Inh1: LC50/4H (rat) : >5,000mg/m

Eye: Minor irritant
Dermal: Minor irritant

Exposure Limits in Air:
ACGIH/TLV TWA OSHA PEL TWA
5MG/M3 5MG/M3
OSHA PEL STEL
None Established
ACGIH TLV STEL CAL OSHA TWA
10MG/M3 5MG/M3

Revision Number: 1.0

Revision Date: Sept. 05

MSDS Number: 00001

NDA - No Data Available

NA - Not Applicable

4. FIRST AID MEASURES

Contact with EYES:	Immediately flush with large quantities of cool water for at least 15 minutes. Get medical attention.
Contact with SKIN:	Wash off with soap and water.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.
Ingestion:	Do NOT induce vomiting. Drink 4 to 8 ounces of water and see medical attention.
Dermal:	Do not use gasoline's, thinners or solvents to remove product from skin. Wipe material from skin and remove contaminated clothing. Wash with soap and water, and if necessary a waterless skin cleaner.
Injection:	Subcutaneous injection is medical emergency. Seek medical aid immediately.

5. FIRE FIGHTING MEASURES

Flashpoint , CC, °F (°C)	360 ° (182°)
Fire Point, CC, °F (°C)	435° (224°)
Flammable Limits:	Lower: 1 % volume (mist) Upper: 10% volume (mist)
Fire Extinguishing Agents:	Carbon Dioxide, foam, dry chemical
Special Fire Fighting Procedures:	None
Unusual Fire or Explosion Hazard	Material may burn, but not ignite readily

5. ACCIDENTAL RELEASE MEASURES

CHEMTREC EMERGENCY NUMBER (24 hr); (800)424-9300 or (202)483-7616
ACCIDENTAL RELEASE MEASURES:

Spills or Leaks:	Contain any spills with absorbents to prevent migrations and entry into sewers or streams. Take up small spills with dry chemical absorbent, rags, or clay absorbent. Place into containers for later removal. Large spills contain spill in earthen dikes for later recovery. Report such spills as required to appropriate authorities.
Waste Disposal:	It is the responsibility of the user to determine if the material is hazardous waste at the time of disposal. Check before disposing to be sure you are in compliance with all applicable laws and regulations. Chemtrec/RCRA Emergency Hotline Number: (800) 424-9300
Right-to-Know:	None
Protective Measures During Repair and Maintenance of Contaminated Equipment:	Refer to Special Protection Information. Wash exposed skin thoroughly with soap and water. Avoid prolonged contact with used oil. Remove soiled clothing. Use oil impervious gloves if frequent or prolonged contact is expected.
TSCA:	This material is in compliance with the Toxic Substances Control Act (15USC2601-2629)

Revision Number: 1.0

Revision Date: Sept. 05

MSDS Number: 00001

NDA - No Data Available

NA - Not Applicable

7. HANDLING AND STORAGE

Keep containers sealed until ready for use. Avoid excessive long-term storage temperatures to prolong shelf life. Maximum storage temperature: 120F. Store in well ventilated areas.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation (Local, Mechanical, Special): Use in a well ventilated area with local exhaust ventilation.
Respiratory Protection: None required in normal use. Use only NIOSH/MSHA Organic vapor approved equipment if necessary.
Gloves: Not required in normal use.
Eye Protection: Goggles or safety glasses are recommended.
Other Protective Equipment: Practice good personal hygiene. Wash hands after use and handling.

Ventilation Requirements: Use in well ventilated area. In confined space, mechanical ventilation may be required to keep levels of certain components below mandated standards, as evaluated by designated personnel. Keep away from heat, sparks and flames.

Respiratory: Normally none required. If high vapor or mist concentrations expected – use respirator approved for organic vapors and mists.

Eyes: Avoid contact with eyes. Safety goggles, or chemical splash goggles if splashing is anticipated. Contact Lenses should not be worn.

Dermal: Oil impervious gloves if frequent or prolonged contact is expected. Barrier creams that are specific for oil based materials are recommended when gloves are impractical.

Other Clothing or Equipment: Wear body-covering work clothes to avoid prolonged or repeated exposure. Launder soiled work clothes before reuse. It is suggested that a source of clean water be available in work area for flushing eyes and skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name:

Form: Amber Liquid

Revision Number: 1.0

Revision Date: Sept. 05

MSDS Number: 00001

NDA - No Data Available

NA - Not Applicable

Odor:	No Odor
Specific Gravity (water = 1):	0.85 - 0.88
Melting Point:	NE
Boiling Point, 760 mmHg, °F (°C):	-600°F (-316°C)
Volatility, weight % at 25C:	Negligible
Evaporation Rate:	Slower than Ether
Vapor Pressure, mmHg at 20C:	<0.001 mmHg
Solubility in Water:	Insoluble
Pour Point:	10°F
API Gravity:	29°F - 31°F
Vapor Density (Air = 1)	>1
Density:	7.1 lb/gal
Molecular Weight:	>460
How to detect this substance:	Viscous only. Amber colored liquid with a characteristic petroleum odor and slippery feel.
Stability:	Stable
Combustible:	No
Flammable:	No
Pyrophoric:	No
Compressed Gas:	No
Organic Peroxide:	No
Reactivity:	No
Explosive:	No
Oxidizer:	No

10. STABILITY AND REACTIVITY

Reactivity:	Stable under normal temperatures and pressures.
Incompatibilities:	Strong oxidants.
Hazardous Polymerization:	None.
Hazardous Decomposition Products:	Thermal decomposition in the presence of air may yield major amounts of oxides of carbon and minor amounts of oxides of sulfur and nitrogen..

Unusual Fire and Explosion Hazards: Move container from fire area if you can do so without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from ends of tanks and drums – Heated containers may rupture, explode or be thrown into the air. Heated vapors may be sensitive to static discharge, resulting in fire or explosion.

Fire Fighting Procedures: Withdraw immediately in case of rising sound from venting safety device or discoloration of tank due to fire. Keep storage containers cool with water spray. Use self-contained breathing apparatus (SCBA).

11. TOXICOLOGICAL INFORMATION

Revision Number: 1.0

Revision Date: Sept. 05

MSDS Number: 00001

NDA - No Data Available

NA - Not Applicable

Inhalation: Low risk of inhalation at ambient temperatures. Mists or fumes may cause drowsiness, dizziness, headache, nausea, or lung irritation or chemical pneumonitis. High concentrations of vapor or mist may be irritating to the respiratory tract. Including nose and throat, may cause difficulty breathing.

Dermal Contact: Transient, slight irritant, possible mild allergen. Prolonged or repeated contact may cause redness. Contact with hot material may cause thermal burns.

Eye Contact: May be mildly irritating. Direct contact may cause burning, tearing and redness. Contact with hot material may cause thermal burns.

Ingestion: Low toxicity. At a Saybolt viscosity of 170 SUS (100°F), the risk of aspiration into the lungs is reduced. If less than 1oz is ingested, material may pass through the system without harm. On ingestion of large quantities, slight GI discomfort, diarrhea, and headache may occur. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death. Human lethal dose - 1 pint.

Injection: Subcutaneous or intramuscular injection may cause irritation, erythema, edema.

Chronic Exposure: Prolonged and/or frequent contact may cause drying, cracking (dermatitis) or folliculitis. High oil mist concentrations may lead to oil pneumonia.

Other Special Effects: None

12. ECOLOGICAL INFORMATION

This product does not contain toxic chemicals of Section 313 of Title III of Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

13. DISPOSAL CONSIDERATIONS

Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative

Revision Number: 1.0

Revision Date: Sept. 05

MSDS Number: 00001

NDA - No Data Available

NA - Not Applicable

or local environmental or health authorities for approved disposal or recycling methods.

14. TRANSPORT INFORMATION

D.O.T. Shipping Name:	Not Regulated
D.O.T. I.D. Number:	NA
Reportable Quantity:	NA
Freight Classification:	NA
UN Hazard Class:	NA
Special Transportation Notes:	None

Notes: NA = Not Applicable
NE = Not Established

15. REGULATORY INFORMATION

SARA 311 CATEGORIES:

1. Immediate (Acute) Health Effects:	NO
2. Delayed (Chronic) Health Effects:	NO
3. Fire Hazard:	NO
4. Sudden Release of Pressure Hazard:	NO
5. Reactivity Hazard:	NO

Section 302/(A) – Extremely Hazardous Substances:

This product does not contain Extremely Hazardous Substances of Section 302/(A)

Clean Water Act:

Under Section 311 (b) of the Clean Water Act, discharges or crude oil and petroleum products in any kind of form to surface waters must be immediately reported to the National Response Center: 800-424-8802.

Comprehensive Environmental, Response, Compensation and Liability Act (CERCLA) – Section 102 Hazardous Substances:

Petroleum and petroleum fractions are excluded from the list of CERCLA hazardous substances by Section 101 (14) of CERCLA.

California Prop 65:

This product may contain chemicals known to the State of California to cause cancer (See also the Health Hazard Information Section).

16. OTHER INFORMATION

NFPA RATINGS: Health 0; Flammability 1; Reactivity 0;

Revision Number: 1.0

Revision Date: Sept. 05

MSDS Number: 00001

NDA - No Data Available

NA - Not Applicable

HMIS RATINGS: Health 1; Flammability 1; Reactivity 0; (0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

REVISION STATEMENT:

This revision updates Section 12 (Ecological Information).

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

- TLV - Threshold Limit Value
- STEL - Short-term Exposure Limit
- RQ - Reportable Quantity
- C - Ceiling Limit
- A1-5 - Appendix A Categories
- NDA - No Data Available
- TWA - Time Weighted Average
- TPQ - Threshold Planning Quantity
- PEL - Permissible Exposure Limit
- CAS - Chemical Abstract Service Number
- () - Change Has Been Proposed
- NA - Not Applicable

Prepared according to the OSHA Hazard Communication Standard

(29 CFR 1910.1200) and the ANSI MSDS Standard (Z400.1).

Revision Number: 1.0

Revision Date: Sept. 05

MSDS Number: 00001

NDA - No Data Available

NA - Not Applicable